



PK 640 T

TECHNICAL SPECIFICATIONS

MODEL N°	HSR316-6
Load rating	40W
Transformer taps	40-20-10-5W
Frequency range	60-22 KHz
Speaker	6,5" Kevlar cone
Tweeter	1" silk
SPL (@1W/m)	88dB
Dimension	252 x 240 mm
Color	White or black

- ▶ High-performance suspended speaker for open-ceiling applications
- ▶ Weather-resistant for use under eaves and in semi-enclosed spaces
- ▶ 5.25"/6.5" polypropylene woofer with damped cloth surround for tight, controlled bass and clear midrange
- ▶ Optimized dual front ports for enhanced low-frequency response
- ▶ Wide-dispersion, horn-loaded titanium dome tweeter for crisp, clear high-end and enhanced pattern control
- ▶ Built-in 30/40 watt 70/100V multi-tap transformer
- ▶ 125 watts program power handling at 8 Ohms
- ▶ 70Hz-20kHz frequency response
- ▶ 100° nominal coverage pattern
- ▶ Rigid glass fiber reinforced ABS construction
- ▶ Magnetically attached steel frameless grille
- ▶ Available in black or white
- ▶ Paintable to blend with surroundings
- ▶ Includes wire rope hanger assembly