



MA5-260



TECHNICAL SPECIFICATIONS

MODEL N°	MA5-260
Rated Power Output	260W
Output Regulation	Less than 3 dB (no load to full load)
Frequency Response	60 - 15,000 Hz, +/- 3dB
THD	Less than 0.5% at 1kHz (1/3 Rated Power)
S/N Ratio	Better than 73dB
Tone Controls	BASS: 100 Hz (+/- 10dB), TREBLE: 12k Hz (+/- 10dB)
Controls	5 input gain, 1 treble, 1 bass, 1 mute, and power switch
Cooling	Internal 12VDC fan, extensive heat sinking
Indicators	Power indicator LED, LED output level meter 0, 2, 4, 6, 8, 10dB
Protection	Fuse: T8.0A
Power Consumption	435W
Power Requirements	220-240V AC, 50/60 Hz
Dimensions	89(H) x 483(W) x 366(D) mm
Built-in Dimensions	2 U rack 19 inch
Carton Dimensions	185(H) x 520(W) x 435(D) mm
Net Weight	13.68kg
Gross Weight	15.32kg
Finish	Panel: steel plate, black Case: steel plate, black

- ▶ Mic 1 with priority in the front
- ▶ 3 microphone and 2 auxiliary inputs
- ▶ 1 line output
- ▶ 100V, 70V and 4-16 Ohms transformer isolated speaker outputs
- ▶ Automatic mute function for paging and announcements
- ▶ Individual input gain controls with master volume control
- ▶ EMC Microphone with priority
- ▶ Bass and treble tone controls
- ▶ LED level meter
- ▶ Speaker output short circuit protection