



## AMP-4600

### TECHNICAL SPECIFICATIONS

MODEL N°	AMP-4600
Rated Power Output	4*600W
Output Regulation	100V, (33k ohm, 1Khz)
Frequency Response	20 - 20,000 Hz, less than 0.1%
THD	Less than 0.1% at 20 - 20,000 Hz
S/N Ratio	Better than 90dB
Tone Controls	10k Ohm unbalance, 20k ohm balance; input sensitivity + 4 dB (1.23V)
Controls	Volume control for each channel
Cooling	Cooling fan, extensive heat sinking
Indicators	Power indicator LED, LED for signal, Peak and protect
Protection	Amplifier: DC output, overheat, over current and short circuits Power supply: Overheat and AC overload
Power Consumption	2880W
Power Requirments	220-240V AC, 50/60 Hz
Dimensions	100v line, M4 screw terminal
Built-in Dimensions	1 U rack 19 inch
Carton Dimensions	185(H) x 520(W) x 435(D) mm
Net Weight	8 kg

- ▶ High efficient at 80 to 90% conversion rate
- ▶ Light weight and compact 1U design
- ▶ Ground connectiong
- ▶ Reliability. Each channel has individual power supply to ensure the highest standard
- ▶ Individual volume control for each channel
- ▶ LED level meter
- ▶ Speaker output short circuit protection